


Creatherm Technical Detail : RC/PW/01.11

[Outputs: 90/70/20 Δt 60°C EN442]

[Dimensions in millimetres]

Radiator Centre Ltd : 2 Grand Parade, Polegate, East Sussex, BN26 5HG
 www.radiatorcentre.com : info@radiatorcentre.com : Tel 01323 486848 : Fax 01323 486687



Model	Output* ÄT=60K Wa tts	n	Water Content litres	Weight kg	Height ± 2mm	Length ± 2mm	Tapping Centres ± 2mm
CV 60-57	591	1.28	4.0	8	600	570	494
CV 60-76	788	1.28	4.8	11	600	760	684
CV 60-91	944	1.28	6.2	12	600	912	836
CV 60-1 14	1182	1.28	7.9	15	600	1140	1064
CV 60-136	1410	1.28	9.4	18	600	1368	1292
CV 150-22	534	1.30	3.8	7	1500	228	152
CV 150-30	711	1.30	5.0	9	1500	304	228
CV 150-38	900	1.30	6.3	12	1500	380	304
CV 150-45	1066	1.30	7.5	14	1500	456	380
CV 180-15	423	1.31	3.0	6	1800	152	76
CV 180-22	620	1.31	4.5	8	1800	228	152
CV 180-30	846	1.31	6.0	11	1800	304	228
CV 180-38	1071	1.31	7.5	14	1800	380	304
CVD 150-22	809	1.32	4.8	9	1500	228	152
CVD 150-30	1079	1.32	7.2	14	1500	304	228
CVD 150-38	1348	1.32	9.5	18	1500	380	304
CVD 150-45	1618	1.32	11.9	23	1500	456	380
CVD 180-15	637	1.33	5.7	11	1800	152	76
CVD 180-22	956	1.33	8.6	17	1800	228	152
CVD 180-30	1274	1.33	11.4	22	1800	304	228
CVD 180-38	1593	1.33	14.3	28	1800	380	304

* for chrome finish reduce shown output by 20%

Creatherm Technical Detail : RC/PW/01.11

[Outputs: 90/70/20 Δt 60°C EN442]

[Dimensions in millimetres]