


Pipe centres from wall = 54mm
 Overall projection = 94mm



Pipe centres: width of radiator - 40mm


Colour options:
 RAL:1001,1013,1015,1016,1021,2003,3
 000,3003,3015,5002,5012,5014,5017,6
 019,6027,7035,7042,8011,9001
 9005,9006,9010

RT25 Technical Detail : RC/PW/01.11

[Outputs: 90/70/20 Δt 60°C EN442]

[Dimensions in millimetres]

Radiator Centre Ltd : 2 Grand Parade, Polegate, East Sussex, BN26 5HG
 www.radiatorcentre.com : info@radiatorcentre.com : Tel 01323 486848 : Fax 01323 486687



Radiator Centre Ltd : 2 Grand Parade, Polegate, East Sussex, BN26 5HG
www.radiatorcentre.com : info@radiatorcentre.com : Tel 01323 486848 : Fax 01323 486687

CODE	Height (mm)	Width (mm)	Depth (mm)	Projection (mm)	Power (watts)
------	-------------	------------	------------	-----------------	---------------

RT25 Single Horizontal

RT25SH2940	296	400	60	94	203
RT25SH3650	368	500	60	94	317
RT25SH5160	512	600	60	94	531
RT25SH5860	584	600	60	94	607
RT25SH6560	656	600	60	94	683
RT25SH2970	296	700	60	94	353
RT25SH3670	368	700	60	94	442
RT25SH5170	512	700	60	94	620
RT25SH4410	440	1000	60	94	759
RT25SH5110	512	1000	60	94	886
RT25SH5810	584	1000	60	94	1011
RT25SH6510	656	1000	60	94	1253
RT25SH2212	224	1200	60	94	455
RT25SH2912	296	1200	60	94	607
RT25SH2914	296	1400	60	94	708
RT25SH3614	368	1400	60	94	886
RT25SH4414	440	1400	60	94	1062
RT25SH2918	296	1800	60	94	860
RT25SH3618	368	1800	60	94	1138
RT25SH4418	440	1800	60	94	1366
RT25SH5118	512	1800	60	94	1593
RT25SH4420	440	2000	60	94	1518
RT25SH5120	512	2000	60	94	1770
RT25SH5820	584	2000	60	94	2023
RT25SH6520	656	2000	60	94	2276
RT25SH2922	296	2200	60	94	1112
RT25SH4422	440	2200	60	94	1669

CODE	Height (mm)	Width (mm)	Depth (mm)	Projection (mm)	Power (watts)
------	-------------	------------	------------	-----------------	---------------

RT25 Double Horizontal

RT25DH2940	296	400	85	94	334
RT25DH3650	368	500	85	94	508
RT25DH5160	512	600	85	94	826
RT25DH5860	584	600	85	94	940
RT25DH6560	656	600	85	94	1052
RT25DH2970	296	700	85	94	585
RT25DH3670	368	700	85	94	963
RT25DH2171	512	700	85	94	712
RT25DH4410	440	1000	85	94	1199
RT25DH5110	512	1000	85	94	1376
RT25DH5810	584	1000	85	94	1566
RT25DH6510	656	1000	85	94	1752
RT25DH2212	224	1200	85	94	787
RT25DH2912	296	1200	85	94	1002
RT25DH2914	296	1400	85	94	1169
RT25DH3614	368	1400	85	94	1423
RT25DH4414	440	1400	85	94	1678
RT25DH2918	296	1800	85	94	1504
RT25DH3618	368	1800	85	94	1830
RT25DH4418	440	1800	85	94	2156
RT25DH5118	512	1800	85	94	2477
RT25DH4420	440	2000	85	94	2396
RT25DH5120	512	2000	85	94	2752
RT25DH5820	584	2000	85	94	3133
RT25DH6520	656	2000	85	94	3505
RT25DH2922	296	2200	85	94	1837
RT25DH4422	440	2200	85	94	2635