



This is the most popular of all steel tube models offering both simplicity and great output. The RT 25 gives you modern design, as well as huge flexibility from a single product range. It can be single or double 25mm tubes, mounted either vertically or horizontally (h), allowing the user to specify the exact model to suit their heating requirement. Similar to the RT 13, but with 25mm tubes, the RT 25 comes in a select range of colours

Specifications

Models Available	70
Materials	Steel
Standard Finish	White
Connections	1/2" BSP
Delivery Details	Stock items (Highlighted): 3-5 working days Colours and orders: 6-8 weeks
Guarantee	5 years
Output Range	437 - 3581W
Stock availability	Highlighted models in stock

Colour options:
RAL:1001,1013,1015,1016,1021,2003,3
000,3003,3015,5002,5012,5014,5017,6
019,6027,7035,7042,8011,9001
9005,9006,9010



designer


[Outputs: 90/70/20 Δt 60°C EN442]

[Dimensions in millimetres]

Radiator Centre Ltd : 2 Grand Parade, Polegate, East Sussex, BN26 5HG
www.radiatorcentre.com : info@radiatorcentre.com : Tel 01323 486848 : Fax 01323 486687

CODE	Height (mm)	Width (mm)	Depth (mm)	Projection (mm)	Power (watts)
RT25 Single Vertical					
RT25SV4029	400	296	60	94	222
RT25SV5036	500	368	60	94	336
RT25SV5044	500	440	60	94	403
RT25SV7029	700	296	60	94	362
RT25SV7036	700	368	60	94	454
RT25SV7051	700	512	60	94	635
RT25SV7058	700	584	60	94	726
RT25SV1044	1000	440	60	94	751
RT25SV1065	1000	656	60	94	1126
RT25SV1222	1200	224	60	94	443
RT25SV1229	1200	296	60	94	592
RT25SV1236	1200	368	60	94	740
RT25SV1244	1200	440	60	94	888
RT25SV1251	1200	512	60	94	1036
RT25SV1258	1200	584	60	94	1183
RT25SV1522	1500	224	60	94	531
RT25SV1529	1500	296	60	94	707
RT25SV1536	1500	368	60	94	884
RT25SV1544	1500	440	60	94	1062
RT25SV1822	1800	224	60	94	609
RT25SV1829	1800	296	60	94	812
RT25SV1836	1800	368	60	94	1015
RT25SV1844	1800	440	60	94	1218
RT25SV1851	1800	512	60	94	1420
RT25SV1858	1800	584	60	94	1624
RT25SV2022	2000	224	60	94	672
RT25SV2029	2000	296	60	94	895
RT25SV2036	2000	368	60	94	1119
RT25SV2044	2000	440	60	94	1343
RT25SV2051	2000	512	60	94	1566
RT25SV2058	2000	584	60	94	1790
RT25SV2065	2000	656	60	94	2013
RT25SV2229	2200	296	60	94	978
RT25SV2236	2200	368	60	94	1223
RT25SV2251	2200	512	60	94	1712

CODE	Height (mm)	Width (mm)	Depth (mm)	Projection (mm)	Power (watts)
RT25 Double Vertical					
RT25DV4029	400	296	60	94	341
RT25DV5036	500	368	60	94	527
RT25DV5044	500	440	60	94	632
RT25DV7029	700	296	60	94	561
RT25DV7036	700	368	60	94	689
RT25DV7051	700	512	60	94	983
RT25DV7058	700	584	60	94	1123
RT25DV1044	1000	440	60	94	1139
RT25DV1065	1000	656	60	94	1708
RT25DV1222	1200	224	60	94	664
RT25DV1229	1200	296	60	94	886
RT25DV1236	1200	368	60	94	1107
RT25DV1244	1200	440	60	94	1329
RT25DV1251	1200	512	60	94	1551
RT25DV1258	1200	584	60	94	1771
RT25DV1522	1500	224	60	94	802
RT25DV1529	1500	296	60	94	1069
RT25DV1536	1500	368	60	94	1337
RT25DV1544	1500	440	60	94	1604
RT25DV1822	1800	224	60	94	891
RT25DV1829	1800	296	60	94	1275
RT25DV1836	1800	368	60	94	1594
RT25DV1844	1800	440	60	94	1913
RT25DV1851	1800	512	60	94	2231
RT25DV1858	1800	584	60	94	2550
RT25DV2022	2000	224	60	94	1021
RT25DV2029	2000	296	60	94	1361
RT25DV2036	2000	368	60	94	1702
RT25DV2044	2000	440	60	94	2042
RT25DV2051	2000	512	60	94	2382
RT25DV2058	2000	584	60	94	2723
RT25DV2065	2000	656	60	94	3062
RT25DV2229	2200	296	60	94	1474
RT25DV2236	2200	368	60	94	1842
RT25DV2251	2200	512	60	94	2580



Radiator Centre Ltd : 2 Grand Parade, Polegate, East Sussex, BN26 5HG

[RT25 Vertical] Round Tube Steel Radiator

[Jan 2011]

[Outputs: 90/70/20 At 60°C EN442]

[Dimensions in millimetres]