



Exclusive Exclusive Exclusive :



The unobtrusive Versatile Convector radiator is ideally suited to situations where windows reach almost down to the floor. Wall or floor mounted, this discreet radiator produces a high heat output for such a compact system.

This bespoke range is available in 16 standard configurations, and 16 high output versions. Priced "per metre", it is available from 500mm to 6000mm in 100mm increments.

Specifications


Models Available	32 models in any length
Materials	Steel
Standard Finish	White
Connections	1/2" BSP
Delivery Details	Bespoke items: 35 working days
Guarantee	5 years
Output Range	218 - 23910W
Stock availability	Non stock bespoke product

Optional grilles for convectors (factory fitted).




NR19500 - A 10% reduction in heat output can be expected from this grille type.

Wall Bracket




Floor Bracket



Radiator Centre Ltd : 2 Grand Parade, Polegate, East Sussex, BN26 5HG
WWW.radiatorcentre.com : info@radiatorcentre.com : Tel 01323 486848 : Fax 01323 486687

[Outputs: 90/70/20 Δt 60°C EN442]


[Dimensions in millimetres]




[Versatile Convector]					
CODE	Height (mm)	Width (mm)	Depth (mm)	Projection (mm)	Power p/mtr (watts)
Standard configurations					
VC7-2	70	500-6000	73	103	436
VC7-3	70	500-6000	134	164	759
VC7-4	70	500-6000	196	226	1040
VC7-5	70	500-6000	256	286	1249
VC14-2	140	500-6000	73	103	637
VC14-3	140	500-6000	134	164	1172
VC14-4	140	500-6000	196	226	1618
VC14-5	140	500-6000	256	286	1925
VC21-2	210	500-6000	83	113	908
VC21-3	210	500-6000	154	184	1505
VC21-4	210	500-6000	226	256	2082
VC21-5	210	500-6000	296	326	2610
VC28-2	280	500-6000	83	113	1111
VC28-3	280	500-6000	154	184	1833
VC28-4	280	500-6000	226	256	2537
VC28-5	280	500-6000	296	326	3179
Floor Bracket (Each)	2 x required for lengths up to 2000mm 1 x further bracket required for each additional 2000mm				
Wall Bracket (Each)	2 x required for lengths up to 2000mm 1 x further bracket required for each additional 2000mm				

[Versatile Convector] high output					
CODE	Height (mm)	Width (mm)	Depth (mm)	Projection (mm)	Power p/mtr (watts)
High Output configurations					
VCP7-2	70	500-6000	92	122	483
VCP7-3	70	500-6000	173	203	810
VCP7-4	70	500-6000	254	284	1090
VCP7-5	70	500-6000	335	365	1419
VCP14-2	140	500-6000	92	122	801
VCP14-3	140	500-6000	173	203	1359
VCP14-4	140	500-6000	254	284	1906
VCP14-5	140	500-6000	335	365	2433
VCP21-2	210	500-6000	92	122	1078
VCP21-3	210	500-6000	173	203	1833
VCP21-4	210	500-6000	254	284	2592
VCP21-5	210	500-6000	335	365	3301
VCP28-2	280	500-6000	92	122	1305
VCP28-3	280	500-6000	173	203	2213
VCP28-4	280	500-6000	254	284	3133
VCP28-5	280	500-6000	335	365	3986
Floor Bracket (Each)	2 x required for lengths up to 2000mm 1 x further bracket required for each additional 2000mm				
Wall Bracket (Each)	2 x required for lengths up to 2000mm 1 x further bracket required for each additional 2000mm				

Grille options	
C2	NR19100 Grille
C3	NR19100 Grille
C4	NR19100 Grille
C5	NR19100 Grille
C2 / CP2	NR19500 Grille (10% reduction in output can be expected from this grille type)
C3 / CP3	NR19500 Grille (10% reduction in output can be expected from this grille type)
C4 / CP4	NR19500 Grille (10% reduction in output can be expected from this grille type)
C5 / CP5	NR19500 Grille (10% reduction in output can be expected from this grille type)



NR19100 Type C only



NR19500 Type C & Type CP

[Outputs: 90/70/20 Δt 60°C EN442]

[Dimensions in millimetres]

Radiator Centre Ltd : 2 Grand Parade, Polegate, East Sussex, BN26 5HG
 WWW.radiatorcentre.com : info@radiatorcentre.com : Tel 01323 486848 : Fax 01323 486687