



All dimensions shown are in millimetres

- Test pressure: 12 BAR
- Max working pressure: 8 BAR
- Max working temperature: 100° C
- All steel construction: oval 60mm x 30mm x 1.5mm tubes
dia 25mm x 2mm headers
- Connections: ½ inch BSP bottom opposite end tapings

Heat output determined in accordance with EN 442

Model	Output* ÄT=50K Watts	Output* ÄT=60K Watts	n	Water Content litres	Weight kg	Height ± 2mm	Length ± 2mm	Tapping Centres ± 2mm	Fixing Centres	
									V ±2mm	H ±2mm
PE 60-62	520	659	1.29	5.8	11	600	620	n/a	550	499
PE 60-83	696	882	1.29	7.8	14	600	830	n/a	550	709
PE 60-104	873	1105	1.29	9.7	17	600	1040	n/a	550	919
PE 150-27	470	595	1.29	6.5	11	1500	270	n/a	1450	149
PE 150-34	587	744	1.29	8.1	14	1500	340	n/a	1450	219
PE 150-41	705	892	1.29	9.7	16	1500	410	n/a	1450	289
PE 180-27	557	705	1.29	7.8	14	1800	270	n/a	1750	149
PE 180-34	696	882	1.29	9.7	16	1800	340	n/a	1750	219
PE 180-41	836	1058	1.29	11.6	19	1800	410	n/a	1750	289

* for chrome finish reduce shown output by 20%

